C42892

999

NEW

Std

PLAN NSP

S13B

Exp. 3-31-06

Vertical reinforcement	Axis of sign
Ground surface away from traffic	SECTION B-B
	Base R Elev 100 Max mortar 65 Min Ground surface adjacent to traffic
epth edestal = 2.5 m :16 @ 89 mm pitch 762 mm to Template	Conduit, see Lighting Plan See "Anchorage Details" on New Std Plan NSP S2A and see NSP S2B. #16 @ 89 mm Pedestal vertical reinforcement, See table for size Place concrete against undisturbed material Permissible Const joint Vert Reinf

Pile diameter

See table

SECTION A-A

75 Clr

Vertical reinforcement

equally spaced

(See table)

Spiral #16 @ 89 mm pitch-

Pedestal Vert Reinf

Total 16, see table

Spiral reinforcement

for size

	Anchor Bolts			Round Pedestal					CIDH							
					Reinforcing		Sp	iral		* *	Vertical Reinforcing			Spiral		
Post Type No.	Bolt Circle (mm)	Bolts Total & Dia (mm)	Total Length (mm)	Dia (mm)	Total	Bar Size	Loop Circle (mm)	Bar Size	Pitch (mm)	Pile Dia (mm)	Pile Depth (m)	Total	Bar Size	Bar Circle (mm)	Bar Size	Pitch (mm)
Ш	610	12-51	1270	1600	16	#32	1435	#16	89	1372	4.5	26	#32	1143	#16	89
Ш	610	12-51	1270	1600	16	#32	1435	#16	89	1372	4.9	26	#32	1143	#16	89
IV	610	12-51	1270	1600	16	#32	1435	#16	89	1372	5.5	26	#32	1143	#16	89
٧	864	14-51	1270	1600	16	#32	1435	#16	89	1372	5.8	26	#32	1143	#16	89
VI	864	16-64	1524	1753	16	#36	1581	#16	89	1524	6.7	28	#36	1295	#16	89
VII	864	16-64	1524	1753	16	#36	1581	#16	89	1524	7.0	28	#36	1295	#16	89
VIII	864	16-64	1524	1753	16	#36	1581	#16	89	1524	7.6	28	#36	1295	#16	89
IX	864	16-64	1524	1753	16	#36	1581	#16	89	1524	7.6	28	#36	1295	#16	89

* * Use Foundation Depth shown in table unless otherwise shown on the Project Plans.

NOTES

Ground surface away from traffic

155 Max

25 Min

Slope protection See note 5

Ground surface

75 Clr

Spiral Reinf

adjacent to traffic

DETAIL C

- 1. For anchor bolt layout see post sheet.
- 2. For "Base & elevation" see Project Plans.
- 3. Prior to erection of the post, backfill which is equivalent to the surrounding material shall be in place.
- 4. Pedestal shall be formed 150 mm minimum below ground surface Remainder to be placed against undisturbed material.
- 5. Slope protection required when indicated on the Project Plans.
- 6. Foundation design is based on 2001 AASHTO article 13.6 Broms' approximate procedure assuming a cohesionless material. The angle of internal friction used is 30 degree and unit weight of soil used is 1922 kg/m³.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

OVERHEAD SIGNS-TRUSS SINGLE POST TYPE ROUND PEDESTAL PILE FOUNDATION

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

NSP S13B, NSP S13A, NSP S13C AND NSP S13D DATED DECEMBER 30, 2004 SUPERSEDE RSP S13 DATED OCTOBER 26, 2000 AND STANDARD PLAN S13 DATED JULY 1, 1999-PAGE 232 OF THE STANDARD PLANS BOOK DATED JULY 1999.

NEW STANDARD PLAN NSP S13B

\sim